

ARM-A-DOR® RIM EXIT DEVICES

Features

Three Products in One

- Locking Bar Security
- Panic Exit Device with UL listing U.S. and Canada
- Loss Prevention Alarm (when alarm equipped)



Drop Bar Security

- Provides resistance to forced entry attacks per UL1034 standard
- Locking members extend 1 1/2" over frame on each side

Code Conformance

- UL1034 Forced Entry
- UL 305 Panic Device Rating
- UL 10B, Fire Exit Hardware, 3 hrs. at 2000° F
- Dade County (Florida) Product Control Approved (Hurricane)
- NFPA 101 Life Safety Code
- UBC/BOCA
- ANSI 156.3
- City of New York, Dept. of Buildings, MEA 292-96-E

Works with ANY Security System

- Alarm operated by standard or interchangeable core mortise cylinder
- Optional remote switch operates timed delay egress systems, cameras or other alarms

Alarmed Models

- Battery operated – approx. 1-yr. life; two 9-Volt batteries included
- Low battery audible warning signal
- Loud alarm, 1 horn; 95 db @ 10 ft.
- Tamper Alarm
- Nuisance Alarm
- Re-arm reminder feature
- Optional AC adapter or hardwire kits
- Optional delay arming feature

Flexible Installation

- Quick Install models with pre-assembled 36" and 48" units
- Easy to follow six-step installation instructions
- Retrofit or new construction work
- Non-handed
- Fits doors 36" to 48" wide
- Double-door applications work on fixed or removable center mullions or without mullion
- No special door preparation
- Works on any door or frame
- Shipped with required hardware for standard single door applications

Relocking Choices

- Automatic or manual models

Mechanical Efficiency and Durability

- Roller design deadbolt means reduced friction and wear
- Touch-bar operates with straight push-through motion
- Weather and water resistant

COMPLETE PRODUCT ASSEMBLIES

Product Number	Description	*Alarm	Fits Door Widths	Fits Jambes Up To	Finish
A101-001	Automatic Re-Lock	No	3' to 4'	6 3/4"	US28/628
A101-002	Automatic Re-Lock	Yes	3' to 4'	6 3/4"	US28/628
A101-F01	Automatic-Fire Rated	No	3' to 4'	6 3/4"	US28/628
A101-F02	Automatic-Fire Rated	Yes	3' to 4'	6 3/4"	US28/628
A101-012	36" Automatic Re-Lock	No	3' ONLY	5 3/4" ONLY	US28/628
A101-013	36" Automatic Re-Lock	Yes	3' ONLY	5 3/4" ONLY	US28/628
A101-014	48" Automatic Re-Lock	No	4' ONLY	5 3/4" ONLY	US28/628
A101-015	48" Automatic Re-Lock	Yes	4' ONLY	5 3/4" ONLY	US28/628
A102-001	Manual Re-Lock	No	3' to 4'	6 3/4"	US28/628
A102-002	Manual Re-Lock	Yes	3' to 4'	6 3/4"	US28/628

Optional Kits

A103-003	Alarm Sub-Assembly
A103-002	RX Switch (For wiring to existing systems – one individual kit)
A104-001	Low Profile Installation Kit (For door jambes greater than 6 3/4" up to 12 3/4")
A106-001	Standard Double Door Kit (For door jambes up to 6 3/4")
A106-002	Low Profile Double Door Kit (For door jambes greater than 6 3/4")
A107-001	A/C Adapter Kit (For plug in with battery backup)
A107-002	A/C Adapter Hardwire Kit (For wiring to electrical system with battery backup)

Deadbolts

1881-003	Sliding Deadbolt with Padlock Locking Hasp & Strike
1883-003	Sliding Deadbolt Keylocking with Strike

* Alarm Models A101-002, A101-013, A101-015, A102-002 and A101-F02 require two 9-volt batteries (included) and a standard 1-1/8" mortise cylinder with straight cam (not included).

Stanley Security Solutions, Inc.

6161 E. 75th Street Indianapolis, Indiana 46250

www.stanleysecuritysolutions.com

© 2007 Stanley Security Solutions, Inc. and Stanley Logistics

10M 1107

PHI011