

RIXSON®**ASSA ABLOY**

Heavy-Duty Single-Acting Center Hung Floor Closers

Model 28 Center Hung

Application

- Single Acting, Handed
- Exterior or Interior Doors
- Weight to 350 lbs.
- Centering Arm
- Sizes up to 4'0"x8'6"*
(1219mmx2591mm)



ANSI/C06021

* For doors taller than 8'6" use top pivot # 345 in lieu of 340

Product Description & Features

- Centering arm with adjustment screws in faces of door
- Built-in positive dead stop prevents door from swinging beyond the desired opening degree (*specify 85, 90, 95 or 105°*)
- Separate and independent valves for closing speed, latch speed and backcheck
- Available non-hold open (N) or selective hold open (S) at same degree as dead stop
- Delayed action option – prefix "DA" (*non-hold open closers only*)
- Models available to meet ICC/ANSI A117.1 low opening force requirements, prefix "PH". (*For 8-1/2 lbs. of opening force prefix "PH" and suffix "8-1/2 lbs."*)
- Cold weather fluid option – specify "CWF" (*not available for closers with "DA"*)
- Sealed closer option – specify "SC"
- Available with floor plate or threshold installation (*floor plate shown*)
- Cylolac, rustproof cement case
- Arm reinforcement bracket for wood doors – prefix "W"
- Standard top pivot: #340 included
- Not allowed for fire rated doors
- Frame stop required on the header at the lock side. If not supplied by frame manufacturer, recommend use of 60131 (*see Door Control Accessories page 92*).
- Furnished with wood and machine screws
- Extended spindles available in 1/2" increments up to 2" longer than standard

Technical Information

